

View Online at <https://aerobasegroup.com/nsn/5935-01-064-2405>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.340 inches

**Overall Diameter:**

0.500 inches

**Environmental Protection:**

Moisture resistant and shock resistant and salt water resistant

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd 2nd mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch and bayonet pin

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-c-533, comp 172 federal specification single material response all mating ends single contact grouping or qq-c-530 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Qq-s-365, gr a federal specification single treatment response

**Shell Material Specification:**

Qq-n-626 n0. 360, 1/2 hard federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response all mating ends

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Included Contact Type:**

Round socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold and shell surface silver

**Precious Material And Weight:**

0.010 gold grains, troy and 0.100 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.