

View Online at <https://aerobasegroup.com/nsn/5935-01-064-6291>

Body Style:

Angle shape, external/internal coupling

Overall Length:

Between 0.491 inches and 0.598 inches

Overall Height:

Between 0.557 inches and 0.630 inches

Overall Width:

0.145 inches

Environmental Protection:

Shock proof and vibration proof

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd 2nd mating end

Contact Removability:

Nonremovable 2nd mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Contact Material:

Copper alloy 2nd mating end single contact grouping

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.001 gold grains, troy and 0.100 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.