

View Online at <https://aerobasegroup.com/nsn/5935-01-064-6294>

Body Style:

Right angle type

Overall Length:

Between 4.080 inches and 4.100 inches

Overall Height:

0.593 inches

Overall Width:

0.270 inches

Environmental Protection:

Thermal shock resistant and vibration resistant and shock resistant and humidity resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.067 inches

Distance Between Mounting Facility Centers:

Between 3.765 inches and 3.775 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 ty ii, cl 1 military specification 2nd treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-626 comp 22 federal specification single material response single mating end single contact grouping or qq-b-613 comp 2 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 5 oclock

Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end

Included Contact Quantity:

70 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.070 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.