## NSN 5935-01-064-6826

Thread Class: 2a and 2b

**Body Style:** 

Overall Length:
1.156 inches
Overall Height:
0.688 inches
Overall Width:
0.688 inches

**Thread Direction:** 

Right-hand and right-hand

Straight shape w/cable clamp

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-064-6826

Contan To Contan Distance Detuces Mounting Facilities Devalled To Height
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.500 inches
Cable Entrance Diameter:
0.216 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Threaded Device Type:
Coupling facility and mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
Tnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Compression nut
Thready Qty Per Inch (tpi):
28 and 56
Thread Size:
0.438 inches and 0.099 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-01-064-6826

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Surface Treatment:
Nickel
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.005 gold grains, troy and 0.005 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0