

View Online at <https://aerobasegroup.com/nsn/5935-01-064-8357>

**Body Style:**

Right angle type

**Overall Length:**

5.140 inches

**Overall Width:**

0.285 inches

**Body Height:**

0.330 inches

**Unthreaded Mounting Hole Diameter:**

0.068 inches

**Distance Between Mounting Facility Centers:**

4.940 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 type ii military specification 2nd treatment response single mating end single contact grouping and qq-n-290 cl ii federal specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-613 comp 2 federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

D shape pin left-hand at 6 oclock and d shape pin right-hand at 6 oclock

**Insert Material Specification:**

Mil-p-17091 military specification single material response single mating end

**Included Contact Quantity:**

92 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.092 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.