NSN 5935-01-064-8360

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-064-8360

Body Style: Right angle type **Overall Length:** 5.140 inches **Overall Width:** 0.285 inches **Body Height:** 0.330 inches **Unthreaded Mounting Hole Diameter:** 0.068 inches **Distance Between Mounting Facility Centers:** 4.940 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Guide pin/socket **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Contact Surface Treatment Specification:** Mil-g-45204 type ii military specification 2nd treatment response single mating end single contact grouping and qq-n-290 cl ii federal specification 1st treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-613 comp 2 federal specification single material response single mating end single contact grouping **Guide Design And Location:** D shape pin right-hand at 12 oclock **Insert Material Specification:** Mil-p-17091 military specification single material response single mating end **Included Contact Quantity:**

Included Contact Type:

Round pin single mating end single contact grouping

92 single mating end single contact grouping

NSN 5935-01-064-8360

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.092 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.