AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-064-9183

Body Style:
Right angle type
Overall Length:
2.316 inches
Overall Width:
0.710 inches
Body Height:
0.125 inches
Environmental Protection:
Heat resistant and cold resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end single contact grouping
Connector Locking Method:
Friction
Friction Operating Tempurature Rating:
Operating Tempurature Rating:
Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius
Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location:
Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Side single mating end single contact grouping
Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Side single mating end single contact grouping Contact Material:
Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping
Operating Tempurature Rating: Between -40.0 degrees celsius and 105.0 degrees celsius Terminal Location: Side single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Tin single mating end single contact grouping Insert Material:
Operating Tempurature Rating:Between -40.0 degrees celsius and 105.0 degrees celsiusTerminal Location:Side single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyamide single mating end
Operating Tempurature Rating:Between -40.0 degrees celsius and 105.0 degrees celsiusTerminal Location:Side single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyamide single mating endTerminal Type:
Operating Tempurature Rating:Between -40.0 degrees celsius and 105.0 degrees celsiusTerminal Location:Side single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyamide single mating endTerminal Type:Wire wrap single mating end single contact grouping
Operating Tempurature Rating:Between -40.0 degrees celsius and 105.0 degrees celsiusTerminal Location:Side single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyamide single mating endTerminal Type:Wire wrap single mating end single contact grouping
Operating Tempurature Rating:Between -40.0 degrees celsius and 105.0 degrees celsiusTerminal Location:Side single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyamide single mating endTerminal Type:Wire wrap single mating end single contact groupingIncluded Contact Quantity:15 single mating end single contact grouping
Operating Tempurature Rating:Between -40.0 degrees celsius and 105.0 degrees celsiusTerminal Location:Side single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyamide single mating endTerminal Type:Wire wrap single mating end single contact groupingIncluded Contact Quantity:15 single mating end single contact groupingIncluded Contact Type:
Operating Tempurature Rating:Between -40.0 degrees celsius and 105.0 degrees celsiusTerminal Location:Side single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Tin single mating end single contact groupingInsert Material:Plastic polyamide single mating endTerminal Type:Wire wrap single mating end single contact groupingIncluded Contact Quantity:15 single mating end single contact groupingIncluded Contact Type:Square pin single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2

AeroBase Group

Demilitarization:

No

Fiig:

A039b0