

View Online at <https://aerobasegroup.com/nsn/5935-01-064-9902>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.234 inches

**Overall Diameter:**

1.641 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

21-11 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Thread Length:**

0.219 inches

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.188 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Included Contact Quantity:**

11 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.011 gold grains, troy and 0.011 silver grains, troy

**Precious Material:**

Gold and silver

**Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms27467 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-38999 spec.