Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-065-0007

Thread Class: 2b Thread Direction: Right-hand Overall Length: 0.600 inches Overall Diameter: 0.700 inches Cable Opening Diameter: 0.580 inches Cable Opening Quantity: 1 Stoz Designation: 3 and 10 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 0.500 inches Material: Auminum aloy Style Designator: Straight shape solid type Surface Treatment: Any acceptable Thread Size Designator: Unef Sheft Life: Na Unit Of Measure:			
Tread Direction:         Right-hand         Overall Length:         0.600 inches         Overall Diameter:         0.750 inches         Cable Opening Diameter:         0.586 inches         Cable Opening Quantity:         1         Stor Bosignation:         3 and 10         Mounting Facility Type And Quantity:         1 threaded coupling         Mounting Facility Type And Quantity:         1 threaded coupling         Thread Size:         0.500 inches         Material:         Auminum alloy         Style Designator:         Auge Treatment:         Any acceptable         Thread Size:         Diract Treatment:	Thread Class:		
Right-hand   Overall Length:   0.600 inches   Overall Diameter:   0.750 inches   Cable Opening Diameter:   0.586 inches   Mounting Facility Type And Quantity:   1 threaded coupling   Thread Y Der Inch (tpi):   28   Note of Sacie   1 threaded coupling   Thread Size:   0.500 inches   Material:   Auminum alloy   Style Designator:   Naterial:   Nater			
Overall Length:0.600 inchesOverall Diameter:0.750 inchesCable Opening Diameter:0.586 inchesCable Opening Quantity:1Star Designation:3 and 10Mounting Facility Type And Quantity:1 threaded couplingThread Y Der Inch (tpl):287 Diread Size:0.500 inchesMounting Active Size:0.500 inchesMaterial:Aurinum alloyStyle Designator:Any acceptableThread Size:0.500 inchesMaterial:Aurinum alloyStyle Designator:Chread Size:0.500 inchesMaterial:Aurinum alloyStyle Designator:Chread Series Designator:Interd Series Designator:Nameteriation			
0400 inches 04790 inches 0750 inches 0500			
Overall Diameter:0.750 inchesCable Opening Diameter:0.886 inchesCable Opening Quantity:1Size Designation:3 and 10Mounting Facility Type And Quantity:1 threaded couplingThready Quer Inch (tpi):28Thread Size:0.500 inchesMaterial:Atuming maloyStyle Designator:Straight Shape solid typeSurface Treatment:Any acceptableThread Series Designator:UndefMerial:Any acceptableThread Series Designator:UndefStrifter Shape solid typeSurface Treatment:Any acceptableThread Series Designator:UndefShafe Series Designator:UndefStrifter Shape solid typeSurface Treatment:NaNaStrifter Series Designator:UndefStrifter Series Designator:NaStrifter Series Designator:NaStrifter Series Designator:Strifter Series Designator:Strifter Series Designator:NaStrifter Series Designator:Strifter Series Designator:Str			
0.750 inches Cable Opening Diameter: 0.586 inches Cable Opening Quantity: Cable Opening Quantity: 1 Sace Designation: 3 and 10 Mounting Facility Type And Quantity: 3 and 10 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Thread Size: 0.500 inches Thread Size: 0.500 inches Material: Aluminum alloy Style Designator: Straight shape solid type Surface Treatment: Any acceptable Thread Series Designator: Unit of Measure: Via Unit of Measure: Catle C	0.600 inches		
Cable Opening Diameter:         0.586 inches         Cable Opening Quantity:         1         Size Designation:         3 and 10         Mounting Facility Type And Quantity:         1 threaded coupling         Threaded coupling         Threaded scoupling         Check Size:         0.500 inches         Material:         Aluminum alloy         Style Designator:         Strade Treatment:         Any acceptable         Thread Series Designator:         Und f         Shef Inter:         Na         Unif Of Measure:         Inter Series Designator:         Na         Dint of Measure:         Inter Series Designator:         Na         Dint of Measure:         Inter Series Designator:	Overall Diameter:		
0.886 inches Cable Opening Quantity: I Cable Opening Quantity: I I Size Designation: 3 and 10 Mounting Facility Type And Quantity: 1 threaded coupling Thread Coupling Thread Quy Per Inch (tpi): 28 Thread Size: 1.0500 inches Thread Size: 1.0500 inches Material: 1.0500 inches Material: 1.0500 inches Material: 1.0500 inches Material: 1.0500 inches Style Designator: 1.0500 inches Style Designator: 1.0500 Chef Stel Subsignator:	0.750 inches		
Cable Opening Quantity:         1         Size Designation:         3 and 10         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Oty Per Inch (tpi):         28         Thread Size:         0.500 inches         Material:         Aluminum alloy         Style Designator:         Stratight shape solid type         Nardaet Cable Signator:         Nardaet Seeise Designator:         Outing Segnator:         Stratight shape solid type         Stratight Signator:         Nardaet Seeise Designator:         Undef         Def Life:         Nardaet Seeise Designator:         Undef         Did Measure:            Pamiliarization:         No         Fig:	Cable Opening Diameter:		
1         Size Designation:         3 and 10         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         28         Thread Size:         0.500 inches         Material:         Aluminum alloy         Style Designator:         Stratight shape solid type         Nay acceptable         Thread Series Designator:         Unef         Sheff Life:         Nay         Chef Support         Stratight shape solid type         During         Dired Series Designator:         Unef         Sheff Life:         Nay         Chef Support         Strate Treatment:         Nay         Dired Series Designator:         Unef         Sheff Life:         Nay         The Geries Designator:         Strates Series Designator:	0.586 inches		
Size Designation: 3 and 10 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Thready Cty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: 0.500 inches Material: 1.500 inches 1.500 inches	Cable Opening Quantity:		
3 and 10         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         28         Thread Size:         0.500 inches         Material:         Aluminum alloy         Style Designator:         Stright shape solid type         Any acceptable         Thread Series Designator:         Unef         Sheff Life:         N/a         Unif Of Measure:            Demilitarization:         Na         Fig:	1		
Nounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):2828Thread Size:0.500 inchesMaterial:Aluminum alloyStyle Designator:Style Designator:Nariage solid typeAuriage tableThread Steise Designator:Out of Measure:NaUnefStelf Life:NaDi Cf Measure:-Denilitarization:NaFig:Fig:	Size Designation:		
1 threade coupling   Thready Qty Per Inch (tpi):   28   Thread Size:   0.500 inches   Material:   Aluminum alloy   Style Designator:   Styrface Treatment:   Any acceptable   Thread Series Designator:   Unef   Shelf Life:   Na   Dir of Measure:     Demilitarization:   No   Fig:	3 and 10		
Thready Qty Per Inch (tpi):28Thread Size:0.500 inchesMaterial:Autonium alloyStyle Designator:Straight shape solid typeSurface Treatment:Any acceptableThread Series Designator:UnefShelf Life:NaDint Of Measure:Demilitarization:NoFig:	Mounting Facility Type And Quantity:		
28 Thread Size: 0.500 inches Material: Aluminum alloy Aturiau Aluminum alloy Style Designator: Straight shape solid type Straight shape solid type Strate Treatment: Any acceptable Thread Series Designator: Unef Shelf Life: N/a Dit Of Measure:  Demilitarization: No Fig: i life:	1 threaded coupling		
Thread Size:0.500 inchesMaterial:Aluminum alloyAluminum alloyStyle Designator:Straight shape solid typeSurface Treatment:Any acceptableThread Series Designator:UnefShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):		
0.500 inches Material: Aluminum alloy Aluminum alloy Style Designator: Straight shape solid type Straight shape solid type Surface Treatment: Any acceptable Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Fmillitarization: No	28		
Material:Aluminum alloyAluminum alloyStyle Designator:Straight shape solid typeSurface Treatment:Any acceptableThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Thread Size:		
Aluminum alloy Style Designator: Straight shape solid type Surface Treatment: Any acceptable Thread Series Designator: Unef Shelf Life: N/a Unt of Measure: Demilitarization: No Fig:	0.500 inches		
Style Designator:Straight shape solid typeSurface Treatment:Any acceptableThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:		
Straight shape solid typeSurface Treatment:Any acceptableThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Aluminum alloy		
Surface Treatment: Any acceptable Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Style Designator:		
Any acceptable Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	Straight shape solid type		
Thread Series Designator:   Unef   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Surface Treatment:		
Unef Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Any acceptable		
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Thread Series Designator:		
N/a Unit Of Measure: Demilitarization: No Fig:	Unef		
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:		
 Demilitarization: No Fiig:	N/a		
Demilitarization: No Fiig:	Unit Of Measure:		
No Fiig:			
Fiig:	Demilitarization:		
	No		
A10100	Fiig:		
	A10100		