NSN 5935-01-065-0756

Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-065-0756

	•
Body	Style:
Straigh	nt shape, external coupling w/backshell
Overa	II Length:
1.009 i	inches
Overa	II Height:
1.453 i	inches
Overa	II Width:
1.453 i	inches
Enviro	onmental Protection:
Moistu	re proof and salt water resistant and vibration proof
Unthre	eaded Mounting Hole Diameter:
0.120 i	inches
Cente	r To Center Distance Between Mounting Facilities Parallel To Height:
1.156 i	inches
Distan	nce Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 i	inches
Distan	nce From Mounting Shoulder To Front Face:
Betwe	en 0.442 inches and 0.447 inches
Mating	g End Quantity:
1	
Conta	ct Position Arrangement Style:
20-41	single mating end
Conta	ct Removability:
Remov	vable single mating end single contact grouping
Polari	zation Method:
Key, r	multiple key groove
Insert	Position In Deg:
342.0	
Shell	Туре:
Solid	
Conne	ector Locking Method:
Bayon	et pin
Termi	nal Location:
Back s	single mating end single contact grouping
Conta	ct Material:
Coppe	er alloy single mating end single contact grouping
Conta	ct Surface Treatment:
Gold s	ingle mating end single contact grouping and silver single mating end single contact grouping
Termi	nal Type:
Crimp	single mating end single contact grouping
Shell I	Material:

NSN 5935-01-065-0756

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-n-290, class 2 federal specification single treatment response
Included Contact Quantity:
41 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.041 gold grains, troy and 0.041 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27497 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: