

View Online at <https://aerobasegroup.com/nsn/5935-01-065-2968>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Rectangular shape center screwlock

Overall Length:

1.990 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.718 inches

Overall Height:

1.716 inches

Overall Width:

1.077 inches

Environmental Protection:

Humidity resistant and shock proof and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

108 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Polarization boss

Shell Type:

Solid

Connector Locking Method:

Screw

Thread Length:

0.280 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 1 or 2, class 1 or 2 federal specification single treatment response

Included Contact Quantity:

38 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.038 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28804 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.