

View Online at <https://aerobasegroup.com/nsn/5935-01-065-2970>

Body Style:

Straight shape w/flange

Overall Length:

1.406 inches

Overall Height:

1.578 inches

Overall Width:

1.578 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Distance From Mounting Shoulder To Front Face:

Between 0.638 inches and 0.719 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

22-55 all mating ends

Contact Removability:

Removable all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

55 2nd mating end all contact groupings

Included Contact Type:

Round socket 2nd mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.