

View Online at <https://aerobasegroup.com/nsn/5935-01-065-4250>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.222 inches

Overall Height:

Between 1.335 inches and 1.351 inches

Overall Width:

Between 1.335 inches and 1.351 inches

Environmental Protection:

Moisture proof and salt water resistant and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.116 inches and 0.126 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.057 inches and 1.067 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.057 inches and 1.067 inches

Distance From Mounting Shoulder To Front Face:

Between 0.765 inches and 0.775 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

40-1 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

342.0 and 211.0 and 168.0 and 101.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

28

Thread Size:

1.125 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 1 class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 class 3 military specification single treatment response

Shell Material Specification:

Qq-a-367 t6 federal specification single material response

Included Contact Quantity:

38 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.038 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Specification Data:

81349-mil-c-81511/51 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-15000