Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-065-7464

| Thread Class: |
|---|
| 2a and 2b and 2a |
| Thread Direction: |
| Right-hand and right-hand and right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.900 inches |
| Overall Height: |
| Between 0.570 inches and 0.630 inches |
| Overall Width: |
| 0.360 inches |
| Environmental Protection: |
| Corrosion resistant and heat resistant and moisture resistant |
| Distance Between Mounting Facility Centers: |
| 2.600 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 40 and 40 and 40 |
| Thread Size: |
| 0.125 inches and 0.125 inches and 0.112 inches |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and copper single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |

NSN 5935-01-065-7464

Electrical Receptacle Connector - Page 2 of 2



| ivii-g-45204, type | I, class 1 military specification 1st treatment response single mating end single contact grouping |
|---------------------|--|
| Terminal Type: | |
| Pin single mating | end single contact grouping |
| Contact Material | Specification: |
| Qq-b-750, comp a | , grade a, spring temper federal specification single material response single mating end single contact groupin |
| Insert Material S | pecification: |
| Mil-p-14, type sdi- | 5 military specification single material response single mating end |
| Included Contact | Quantity: |
| 45 single mating e | nd single contact grouping |
| Included Contact | Туре: |
| Round socket sing | le mating end single contact grouping |
| Precious Materia | I And Location: |
| Contact surfaces | gold |
| Precious Materia | I And Weight: |
| 0.045 gold grains, | troy |
| Precious Materia | I: |
| Gold | |
| Thread Series De | signator: |
| Unc and unc and | JNC |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (military S | Standard): |
| | |