Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-065-7477

View Online at https://aerobasegroup.com/nsn/5935-01-065-7477
Body Style:
Straight shape
Overall Length:
3.840 inches
Overall Width:
0.440 inches
Environmental Protection:
Moisture resistant
Unthreaded Mounting Hole Diameter:
0.138 inches
Distance Between Mounting Facility Centers:
3.484 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Copper single mating end single contact grouping and gold single mating end single contact grouping
Copper single mating end single contact grouping and gold single mating end single contact grouping
Copper single mating end single contact grouping and gold single mating end single contact grouping Insert Material:
Copper single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end
Copper single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type:
Copper single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping
Copper single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:
Copper single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum
Copper single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum Shell Surface Treatment:
Copper single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum Shell Surface Treatment: Cadmium

Mil-m-14, type mdg military specification single material response single mating end

# NSN 5935-01-065-7477

Electrical Receptacle Connector - Page 2 of 2



Shell Guide Type And Location Designator:

A slot

#### Included Contact Quantity:

23 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold

#### **Precious Material And Weight:**

0.023 gold grains, troy

#### **Precious Material:**

Gold

### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A039b0

#### Mil-std (military Standard):

Mil-m-14 spec.