Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-065-8276

# Body Style:

Right angle type

## **Overall Length:**

2.350 inches

## **Overall Width:**

Between 0.233 inches and 0.247 inches

### **Body Height:**

Between 0.399 inches and 0.440 inches

## **Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and vibration resistant

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

### **Polarization Method:**

Guide pin/socket

# **Connector Locking Method:**

Friction

Terminal Location:

Side single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## Insert Material:

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Solder stud single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single material specification single material response single material specification single material spe

## Insert Material Specification:

Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single mating end

## **Included Contact Quantity:**

aludad Cantaat Typa

41 single mating end single contact grouping



Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.041 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.