

View Online at <https://aerobasegroup.com/nsn/5935-01-066-1948>

Body Style:

Straight shape, external coupling

Overall Length:

0.697 inches

Overall Height:

0.828 inches

Overall Width:

0.828 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.394 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.394 inches

Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Aug-98 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3 or 4, grade b military specification single treatment response

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.003 gold grains, troy and 0.003 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms27508 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.