

View Online at <https://aerobasegroup.com/nsn/5935-01-066-4913>

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.735 inches

Overall Diameter:

1.551 inches

Environmental Protection:

Corrosion resistant and explosion proof and moisture resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

20-25 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

13.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

10

Thread Size:

1.250 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum

Shell Surface Treatment:

Anodize

Included Contact Quantity:

13 single mating end all contact groupings

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surface silver

Precious Material:

Silver

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0