## NSN 5935-01-066-6239

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-066-6239

**Body Style:** Straight shape **Overall Length:** Between 2.620 inches and 2.650 inches **Overall Height:** 0.727 inches **Overall Width:** Between 0.590 inches and 0.620 inches **Environmental Protection:** Corrosion resistant and moisture proof and shock resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response

Included Contact Quantity:

50 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-01-066-6239

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
8134924308 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No