

NSN 5935-01-066-6278 Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-066-6278 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Hood, side opening w/clamp **Overall Length:** 3.630 inches **Overall Height:** 2.316 inches **Overall Width:** 0.781 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 41 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Jackscrew

Shell Type:

Hood, side opening

**Connector Locking Method:** 

Jackscrew-socket

**Connector Cable Strain Relief Method:** 

Cable clamp

Thready Qty Per Inch (tpi):

32

**Thread Size:** 

0.138 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-066-6278

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



| Insert Material:   |
|--|
| Plastic diallyl phthalate single mating end  |
| Contact Surface Treatment Specification:   |
| Mil-g-45204, type 2, cl 1, gr c or d military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2, |
| type 7 federal specification 2nd treatment response single mating end single contact grouping  |
| Terminal Type:   |
| Solder well single mating end single contact grouping  |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:   |
| Anodize  |
| Shell Surface Treatment Specification:   |
| Mil-a-8625 military specification single treatment response  |
| Insert Material Specification:   |
| Mil-p-19833, type gdi-30f military specification single material response single mating end  |
| Included Contact Quantity:   |
| 41 single mating end single contact grouping   |
| Included Contact Type:   |
| Round socket single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.041 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):   |