

NSN 5935-01-066-6297 Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-066-6297 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Diameter:** 0.312 inches **Environmental Protection:** Vibration resistant and shock resistant and corrosion resistant and moisture resistant **Cable Entrance Diameter:** 0.141 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Crimp type Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Length:

0.100 inches

Thready Qty Per Inch (tpi):

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

NSN 5935-01-066-6297

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 half hard federal specification single material response single mating end single contact grouping

Shell Material:

Steel

Shell Material Specification:

Qq-s-764, cl 303, cond a federal specification single material response

Insert Material Specification:

L-p-403, type 1 federal specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.