# NSN 5935-01-066-6314

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-066-6314

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
2.550 inches
Overall Height:
0.732 inches
Overall Width:
0.250 inches
Distance Between Mounting Facility Centers:
2.350 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

## NSN 5935-01-066-6314

Electrical Receptacle Connector - Page 2 of 2



## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

## **Included Contact Quantity:**

44 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.044 gold grains, troy

## **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

## Demilitarization:

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.