

View Online at https://aerobasegroup.com/nsn/5935-01-066-6322

Qq-p-416, type 2, cl 1 federal specification single treatment response

Th	read Class:
2a	and 2b
Th	read Direction:
Rig	ght-hand
Вс	ody Style:
Ho	od, top opening w/clamp
Ov	verall Length:
3.0	060 inches
Ov	verall Width:
0.5	570 inches
En	vironmental Protection:
Мс	bisture proof and vibration proof
Th	readed Device Type:
Со	upling facility
Ма	ating End Quantity:
1	
Co	ontact Position Arrangement Style:
10	0 single mating end
Ро	larization Method:
Ja	ckscrew and guide pin/socket
Sh	ell Type:
So	lid
Co	onnector Locking Method:
Ja	ckscrew-socket
Co	onnector Cable Strain Relief Method:
Ca	ble clamp
Ca	ble Opening Length:
1.0	000 inches
	ble Opening Width:
0.4	170 inches
	ready Qty Per Inch (tpi):
40	
	read Size:
	12 inches
	sert Material:
	astic diallyl phthalate single mating end
	ell Material:
	uminum alloy
	ell Surface Treatment:
	Idmium
Sh	ell Surface Treatment Specification:
00	n-116 type 2 cl 1 federal specification single treatment response



Insert Material Specification:

Mil-m-14, sdg-f military specification single material response single mating end

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.