

View Online at <https://aerobasegroup.com/nsn/5935-01-067-0893>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/screw locks

**Overall Length:**

0.880 inches

**Overall Height:**

0.630 inches

**Overall Width:**

0.280 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:**

14 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.