## NSN 5935-01-067-0925

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-067-0925

**Body Style:** 

Straight shape, press fit

Overall Length:

0.324 inches

**Overall Diameter:** 

0.125 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Nonstd single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

2.0 single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Spring friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-533 federal specification single material response single mating end single contact grouping

**Shell Material:** 

Copper alloy

**Shell Material Specification:** 

Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round

**Included Contact Type:** 

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-01-067-0925

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.