NSN 5935-01-067-1212

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-067-1212 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Square flange mount **Overall Length:** 1.093 inches **Bushing Diameter:** 0.340 inches **Overall Height:** 0.625 inches **Overall Width:** 0.380 inches **Environmental Protection:** Shock proof and vibration proof Center To Center Distance Between Mounting Facilities Parallel To Height: 0.481 inches **Cable Entrance Diameter:** 0.085 inches **Threaded Device Type:** Coupling facility and mounting hole **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 and 56

Thread Size:

0.250 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-067-1212

Electrical Receptacle Connector - Page 2 of 2



insert material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Thread Series Designator:
Uns and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0