

View Online at <https://aerobasegroup.com/nsn/5935-01-067-2925>

**Body Style:**

Straight shape, external/internal coupling

**Overall Length:**

1.406 inches

**Overall Diameter:**

0.822 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and shock proof

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

N 2nd mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin and internally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end all contact groupings

**End Application:**

Aircraft stratolifter c-135

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.002 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-a-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-a-55339/21 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0