## NSN 5935-01-067-2956

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-067-2956 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Height:** 1.562 inches **Overall Width:** 1.562 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.375 inches **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel **Shell Material Specification:** Qq-a-367 federal specification single material response **Test Data Document:** 

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

## NSN 5935-01-067-2956

Receptacle Dummy Connector - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-c-83723/61 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0