NSN 5935-01-067-6406

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-067-6406

view Offiline at https://derobasegroup.com/his//0900-01-00/-0400
Body Style:
Straight shape, external coupling w/backshell
Overall Height:
1.453 inches
Overall Width:
1.453 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.578 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.578 inches
Distance From Mounting Shoulder To Front Face:
0.317 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:

Cadmium and nickel

NSN 5935-01-067-6406

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantit	ty:
--------------------------	-----

79 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.