## NSN 5935-01-067-7257

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-067-7257

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
2.000 inches
Body Width:
0.363 inches
Body Height:
0.250 inches
Environmental Protection:
Thermal shock resistant
Distance Between Mounting Facility Centers:
1.750 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyester single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2, grade c military specification 1st treatment response single mating end single contact grouping and mil-p-27418

military specification 2nd treatment response single mating end single contact grouping

Qq-c-533, cond 1/2 h federal specification single material response single mating end single contact grouping

**Contact Material Specification:** 

## NSN 5935-01-067-7257

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 30 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.030 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.