Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-067-7904

····· •····· •······ •················
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.490 inches
Overall Height:
0.812 inches
Overall Width:
0.812 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.594 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.594 inches
Distance From Mounting Shoulder To Front Face:
Between 0.708 inches and 0.728 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
40393 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
40.0 and 112.0 and 228.0 and 258.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Length:
0.290 inches
Thready Qty Per Inch (tpi):
20

NSN 5935-01-067-7904

Electrical Receptacle Connector - Page 2 of 3



Thread Size: 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel Shell Surface Treatment Specification: Mil-c-26074, cl 3 or 4, gr b military specification single treatment response **Shell Material Specification:** Qq-a-367 federal specification single material response **Included Contact Quantity:** 3 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unf **Specification Data:** 81349-mil-c-83723/72 government specification Shelf Life:

N/a

Unit Of Measure:

- **Demilitarization:**

Electrical Receptacle Connector - Page 3 of 3



Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.