

View Online at <https://aerobasegroup.com/nsn/5935-01-067-9411>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

1.055 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Environmental Protection:

Shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.718 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.718 inches

Distance From Mounting Shoulder To Front Face:

0.573 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Tnc 1st mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

36

Thread Size:

0.4375 inches and 0.250 inches

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 2 military specification single treatment response single mating end single contact grouping

Contact Material Specification:

Qq-c-530, half hard federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 1078

Shell Material Specification:

Qq-s-763, class 303, cond h federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.