

View Online at https://aerobasegroup.com/nsn/5935-01-067-9460

| Thread Class: | |
|--|---|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Straight shape, external coupling | |
| Overall Length: | |
| 1.094 inches | |
| Overall Height: | |
| 1.181 inches | |
| Overall Width: | |
| 1.181 inches | |
| Environmental Protection: | |
| Moisture proof and salt water resistant and vibration proof | |
| Unthreaded Mounting Hole Diameter: | |
| 0.150 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | |
| 0.906 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width | : |
| 0.906 inches | |
| Distance From Mounting Shoulder To Front Face: | |
| 0.562 inches | |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 14s-7 single mating end | |
| Polarization Method: | |
| Keyway or multiple keyway | |
| Insert Position In Deg: | |
| 0.0 | |
| Shell Type: | |
| Solid | |
| Connector Locking Method: | |
| Externally threaded shell | |
| Thread Length: | |
| 0.391 inches | |
| Thready Qty Per Inch (tpi): | |
| 10 | |
| Thread Size: | |
| 0.875 inches | |



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0