Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-068-1909

R С 7: Т В С С С	Contact Removability: emovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 50.0 single mating end single contact grouping erminal Location: ack single mating end single contact grouping contact Material:
R С 7: Т В С С С	A contact Maximum Ac Voltage Rating In Volts: 50.0 single mating end single contact grouping erminal Location: ack single mating end single contact grouping contact Material:
С 7: В С С С	Contact Maximum Ac Voltage Rating In Volts: 50.0 single mating end single contact grouping erminal Location: ack single mating end single contact grouping contact Material:
7: T B C C	50.0 single mating end single contact grouping erminal Location: ack single mating end single contact grouping contact Material:
т В С С	erminal Location: ack single mating end single contact grouping contact Material:
в С С	ack single mating end single contact grouping contact Material:
с С С	ontact Material:
с с	
С	conner ellev single meting and single contest grouping
	opper alloy single mating end single contact grouping
G	ontact Surface Treatment:
	old single mating end single contact grouping
Т	erminal Type:
W	/ire wrap single mating end single contact grouping
С	ontact Material Specification:
Q	q-b-626, 1/2 hard federal specification single material response single mating end single contact grouping
Ir	ncluded Contact Quantity:
1	04 single mating end single contact grouping
Ρ	recious Material And Location:
С	contacts gold
Ρ	recious Material:
G	old
S	helf Life:
Ν	/a
U	nit Of Measure:
D	emilitarization:
Ν	0
F	iig:
A	039b0