Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-068-5853

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
1.620 inches
Overall Height:
0.840 inches
Overall Width:
0.590 inches
Unthreaded Mounting Hole Diameter:
0.130 inches
Distance Between Mounting Facility Centers:
1.312 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
26 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
750.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1050.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

## NSN 5935-01-068-5853 Electrical Receptacle Connector - Page 2 of 2



**Insert Material:** Plastic melamine mineral filled single mating end **Terminal Type:** Crimp single mating end single contact grouping **Included Contact Quantity:** 26 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.026 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0