Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-069-2564

Body Style:
Flange mount
Bushing Diameter:
2.171 inches
Overall Diameter:
3.500 inches
Environmental Protection:
Corrosion resistant and fire resistant and shock resistant
Unthreaded Mounting Hole Diameter:
0.187 inches
Distance From Mounting Shoulder To Rear Face:
2.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
50.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end all contact groupings
Shell Type:
Solid
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Aluminum single mating end all contact groupings
Insert Material:
Plastic phenolic single mating end
Terminal Type:
Tab, solder lug single mating end all contact groupings
Shell Material:
Steel
Included Contact Quantity:
2 single mating end 2nd contact grouping
Included Contact Type:
Curved bin w/outside lin single mating and 1st contact grouping

Curved pin w/outside lip single mating end 1st contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0