NSN 5935-01-069-6052

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-069-6052

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
1.900 inches
Overall Height:
Between 0.472 inches and 0.487 inches
Overall Width:
0.294 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof
Distance Between Mounting Facility Centers:
1.750 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Inter-contact polarizing keys
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Qq-n-290, cl 1, grade e federal specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2,

grade c, cl 0 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:Tab, solder lug single mating end single contact grouping

NSN 5935-01-069-6052

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Special Features:

Contacts 22, 23, 25, 27 and 28 omitted

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.