Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-069-7244

View Online at https://aerobasegroup.com/nsn/5935-01-069-7244
Body Style:
Multiple card type
Overall Length:
5.953 inches
Overall Height:
1.460 inches
Overall Width:
0.437 inches
Unthreaded Mounting Hole Diameter:
0.178 inches
Distance Between Mounting Facility Centers:
5.630 inches
Board Accommodated Length:
2.656 inches second board
Mating End Quantity:
1
Contact Position Arrangement Style:
Bridged contacts inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping and qq-n-290 federal specification
single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-750 federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14f military specification single material response single mating end
Included Contact Quantity:

30 single mating end single contact grouping



Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.