## NSN 5935-01-069-7627

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-069-7627 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.492 inches **Overall Height:** 0.828 inches **Overall Width:** 0.828 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.594 inches **Distance From Mounting Shoulder To Front Face:** 0.462 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Adem 8-98 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin **Thread Length:** 0.290 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches

**Terminal Location:**Back single mating end single contact grouping

## NSN 5935-01-069-7627

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Material Specification:
Qq-a-367, t6 federal specification single material response
Included Contact Type:
Round pin single mating end single contact grouping
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.