

View Online at <https://aerobasegroup.com/nsn/5935-01-069-8112>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.230 inches

**Overall Diameter:**

1.760 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and vibration proof

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24-61 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

105.0 and 140.0 and 215.0 and 265.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.438 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic epoxy single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Shell Material Specification:**

Qq-a-367 federal specification single material response

**Included Contact Quantity:**

61 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.061 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

81349-mil-c-83723/75 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.