

View Online at <https://aerobasegroup.com/nsn/5935-01-069-9477>

Body Material:

Any acceptable

Body Style:

Bottom mount, radial terminals

Body Diameter:

Between 0.249 inches and 0.251 inches

Mounting Slot Width:

0.018 inches

Overall Diameter:

0.550 inches

Mounting Hole Style:

Slot four mounting holes/slots on bolt circle

Mounting Bolt Circle Diameter:

Between 0.249 inches and 0.251 inches

Contact Material:

Any acceptable

Contact Surface Treatment:

Any acceptable

Accommodated Contact Quantity:

4

Printed Circuit Board Hole Arrangement Style:

Four hole

Component Shield Mounting Method:

Screw

Polarization Type:

Center key hole

Projection Length Below Mounting Surface:

Between 0.093 inches and 0.110 inches

Mounting Method:

Body through hole

Mounting Type For Which Designed:

Printed circuit

Contact Position Arrangement Style:

Square

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-p-7788 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 printed circuit

Specification Data:

96906-ms90335-8 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300

Mil-std (military Standard):

Mil-p-7788 spec.