## NSN 5935-01-070-0518

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-070-0518

view Online at https://aerobasegroup.com/nsn/5935-01-070-0518
Body Style:
Right angle type
Overall Length:
6.750 inches
Overall Width:
0.330 inches
Body Height:
0.410 inches
Unthreaded Mounting Hole Diameter:
0.104 inches
Distance Between Mounting Facility Centers:
6.486 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Contact and mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-613, comp 2, 1/2 hard federal specification single material response single mating end single contact grouping
Income Material Consideration

#### **Insert Material Specification:**

Mil-m-20693, type 1 military specification single material response single mating end

#### **Included Contact Quantity:**

120 single mating end single contact grouping

### **Included Contact Type:**

Flat pin single mating end single contact grouping

# NSN 5935-01-070-0518

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.120 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.