Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-070-1978

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Hood, top opening w/clamp

Overall Length:

2.594 inches

Overall Height:

1.840 inches

Overall Width:

1.188 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

0.550 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

75 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.320 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium Shell Surface Treatment Specification: Qq-p-416 type 2, cl 1 federal specification single treatment response **Insert Material Specification:** Mil-m-14 ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 75 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Item must comply withrequirements of desc production standard no. L02620; for navy nuclear propulsion plant products only **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.075 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.