

View Online at <https://aerobasegroup.com/nsn/5935-01-070-1981>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Hood, top opening w/clamp

Overall Length:

2.366 inches

Overall Height:

2.467 inches

Overall Width:

1.370 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

0.550 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

66 single mating end

Polarization Method:

Jackscrew

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.320 inches and 0.320 inches

Thready Qty Per Inch (tpi):

32 and 32

Thread Size:

0.138 inches and 0.138 inches

Insert Material:

Plastic diallyl phthalate single mating end

Criticality Code Justification:

Feat

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625, type 1 or type 2 military specification single treatment response

Shell Material Specification:

Qq-a-250/8, temper 0 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L02622 for navy nuclear propulsion plant products only

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.