NSN 5935-01-070-1986

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-070-1986

Body Style:
Right angle type
Overall Length:
3.850 inches
Overall Height:
0.550 inches
Overall Width:
0.250 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.600 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-m-14 military specification 1st material response single mating end or mil-p-19833 military specification 2nd material response single
mating end
Unable To Decode:

Included Contact Quantity:

60 single mating end single contact grouping

Unable to decode and unable to decode

NSN 5935-01-070-1986

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.060 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-55302/57 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.