NSN 5935-01-070-6536

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-070-6536 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 3.028 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 2.574 inches and 2.582 inches **Overall Width:** 1.170 inches **Environmental Protection:** Heat resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.558 inches and 0.568 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 51 single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid Thready Qty Per Inch (tpi): Thread Size: 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy

Nickel

Shell Surface Treatment:

NSN 5935-01-070-6536

Electrical Receptacle Connector - Page 2 of 2



Shell	Surface	Treatment	Specification:
SHEH	Juliace	HEAUHEIL	opecincation.

Mil-c-26074, cl 3 or 4, grade b military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

51 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-83733/12 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.