

View Online at <https://aerobasegroup.com/nsn/5935-01-070-7477>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.405 inches

Overall Diameter:

Between 1.136 inches and 1.176 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

40515 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.290 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061 or aluminum alloy 380.0 and aluminum alloy a380.0

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3 or 4, gr b military specification single treatment response

Shell Material Specification:

Qq-a-367, t6 federal specification 1st material response or qq-a-591 federal specification 2nd material response and qq-a-591 federal specification 3rd material response

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3471 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.