Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-071-6139

## **Body Style:**

Straight shape

# **Overall Length:**

Between 1.526 inches and 1.556 inches

## **Overall Height:**

0.684 inches

## **Overall Width:**

Between 0.479 inches and 0.509 inches

## **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

## Distance Between Mounting Facility Centers:

Between 1.307 inches and 1.317 inches

## Mating End Quantity:

**Contact Position Arrangement Style:** 

15 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Polarization Method:**

Mating end

Shell Type:

Solid

1

## **Connector Locking Method:**

Friction

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end single contact grouping

# Criticality Code Justification:

Feat

#### Terminal Type:

Pin single mating end single contact grouping



## Shell Material:

Metal

Shell Surface Treatment:

Cadmium or zinc

# Insert Material Specification:

Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification 2nd material response single mating end

# **Included Contact Quantity:**

15 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

# **Special Features:**

Pin terminal diameter 0.037 min to 0.043 max

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.015 gold grains, troy

# **Precious Material:**

Gold

# **Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-24308/23 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard):

Mil-g-45204 spec.