NSN 5935-01-072-1442

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-072-1442

Body Style: Straight shape **Overall Length:** Between 1.526 inches and 1.556 inches **Overall Height:** 0.625 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Corrosion resistant and moisture proof and shock resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** Between 1.307 inches and 1.317 inches **Mating End Quantity: Contact Position Arrangement Style:** 15 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Spring friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

Included Contact Quantity:

15 single mating end single contact grouping

NSN 5935-01-072-1442

A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/24 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: