NSN 5935-01-072-3893

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-072-3893 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 1.350 inches **Overall Height:** 0.550 inches **Overall Width:** 0.250 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 1.100 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:**

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-072-3893

Electrical Receptacle Connector - Page 2 of 2



ı	n	S	е	rt	M	at	te	ri	al	Ŀ	

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.